






THE MAN TGE.

Technical data.
Valid from 1 March 2019.



DRIVELINE.

Diesel engines	2,0l 75 kW	2,0l 90 kW	2,0l 103 kW	2,0l 130 kW	Electric motor	100 kW
Displacement [cm ³]	1,968	1,968	1,968	1,968	Engine	Permanent magnet synchronous machine
Number of cylinders	4	4	4	4	max. power output [kW (PS)]	100 (136)
max. power output [kW (PS)]	75 (102)	90 (122)	103 (140)	130 (177)	at speed [rpm]	3,300–11,700
at speed [rpm]	3,000–3,500	3,500	3,500–3,600	3,600	max. torque [Nm]	290
max. torque [Nm]	300	300	340	410	at speed [rpm]	0–3,300
at speed [rpm]	1,400–2,250	1,400–2,250	1,600–2,250	1,500–2,000	Nominal capacity [kWh]	35.8
Exhaust-gas category	Euro 6	EURO VI	Euro 6	Euro 6/EURO VI	Fuel type	Electricity
Fuel type	Diesel as per DIN EN 590	Diesel as per DIN EN 590	Diesel as per DIN EN 590	Diesel as per DIN EN 590	Gearbox variant	1-speed gearbox
Gearbox variants	6-speed manual gearbox	6-speed manual gearbox	6-speed manual gearbox 8-speed automatic gearbox ¹	6-speed manual gearbox 8-speed automatic gearbox	max. range [km]	173
Driveline	Front-wheel drive	Rear-wheel drive with twin tyres	Front-wheel drive All-wheel drive Rear-wheel drive with single tyres	Front-wheel drive All-wheel drive Rear-wheel drive with single tyres Rear-wheel drive with twin tyres	Battery	Lithium ion
					Charging	Alternating current (AC) ² Direct current (DC) ³




¹ Only with front-wheel drive.

² Up to 7.2 kW via wall box 5:20 h.

³ Up to 40 kW via CCS 0:45 h to 80%.


DIMENSIONS.

MAN TGE Panel van Standard with Normal roof



Load capacity [m ³]	9.9 ²
Lateral sliding door, width x height [mm]	1,311 x 1,587 ³
Rear hinged doors, clear width x height [mm]	1,552 x 1,605 ⁴
Load deck height at rear [mm]	570 ⁵ (720)
Clearance circle [m]	13.9 – 14.2

MAN TGE Panel van Standard with High roof



Load capacity [m ³]	11.3 ²
Lateral sliding door, width x height [mm]	1,311 x 1,822 ³
Rear hinged doors, clear width x height [mm]	1,552 x 1,840 ⁴
Load deck height at rear [mm]	570 ⁵ (720)
Clearance circle [m]	13.9 – 14.2

Figures for 4x4 and rear-wheel drive with standard roof: 1,626¹/9.3²/1,487³/1,505⁴/670⁵.

Figures for 4x4 and rear-wheel drive with high roof: 1,861¹/10.7²/1,722³/1,740⁴/670⁵.


Figures in brackets: with twin tyres.

All dimensions were measured on series-production vehicles. The heights stated here may vary by approx. ±40 mm depending on fittings. The vehicle drawings are not true to scale.


* Length of the vehicle floor including loading option below the partition. Length in the top area: 3,201 mm.

DIMENSIONS.

MAN TGE Panel van Long with High roof



MAN TGE Panel van Long with Super-high roof



Load capacity [m ³]	14.4 ²
Lateral sliding door, width x height [mm]	1,311 x 1,822 ³
Rear hinged doors, clear width x height [mm]	1,552 x 1,840 ⁴
Load deck height at rear [mm]	570 ⁵ (720)
Clearance circle [m]	16.5 – 17.0


Load capacity [m ³]	16.1 ²
Lateral sliding door, width x height [mm]	1,311 x 1,822 ³
Rear hinged doors, clear width x height [mm]	1,552 x 1,840 ⁴
Load deck height at rear [mm]	570 ⁵ (720)
Clearance circle [m]	16.5 – 17.0

Figures for 4x4 and rear-wheel drive with high roof: 1,861¹/13.6²/1,722³/1,740⁴/670⁵.
 Figures for 4x4 and rear-wheel drive with super-high roof: 2,089¹/15.3²/1,722³/1,740⁴/670⁵.
 Figures in brackets: with twin tyres.


All dimensions were measured on series-production vehicles. The heights stated here may vary by approx. ±40 mm depending on fittings. The vehicle drawings are not true to scale.
 * Length of the vehicle floor including loading option below the partition. Length in the top area: 4,051 mm.

DIMENSIONS.

MAN TGE Panel van Extra-long with High roof



MAN TGE Panel van Extra-long with Super-high roof



Load capacity [m ³]	16.4 ²
Lateral sliding door, width x height [mm]	1,311 x 1,822 ³
Rear hinged doors, clear width x height [mm]	1,552 x 1,840 ⁴
Load deck height at rear [mm]	570 ⁵ (725)
Clearance circle [m]	16.5 – 17.0


Load capacity [m ³]	18.4 ²
Lateral sliding door, width x height [mm]	1,311 x 1,822 ³
Rear hinged doors, clear width x height [mm]	1,552 x 1,840 ⁴
Load deck height at rear [mm]	570 ⁵ (725)
Clearance circle [m]	16.5 – 17.0

Figures for 4x4 and rear-wheel drive with high roof: 1,861¹/15.5²/1,722³/1,740⁴/670⁵.
 Figures for 4x4 and rear-wheel drive with super-high roof: 2,096¹/17.5²/1,722³/1,740⁴/670⁵.
 Figures in brackets: with twin tyres.


All dimensions were measured on series-production vehicles. The heights stated here may vary by approx. ±40 mm depending on fittings. The vehicle drawings are not true to scale.
 * Length of the vehicle floor including loading option below the partition. Length in the top area: 4,606 mm.

DIMENSIONS.

MAN TGE Kombi Standard with Normal roof



MAN TGE Kombi Standard with High roof




Lateral sliding door, width x height [mm]	1,311 x 1,487
Rear hinged doors, clear width x height [mm]	1,552 x 1,505
Max. number of seats	8 + 1
Clearance circle [m]	13.9

Lateral sliding door, width x height [mm]	1,311 x 1,722
Rear hinged doors, clear width x height [mm]	1,552 x 1,740
Max. number of seats	8 + 1
Clearance circle [m]	13.9

All dimensions were measured on series-production vehicles. The heights stated here may vary by approx. ±40 mm depending on fittings. The vehicle drawings are not true to scale. Not available in all countries. Available in different designs.

DIMENSIONS.

MAN TGE Kombi Long with High roof




Lateral sliding door, width x height [mm]	1,311 x 1,722
Rear hinged doors, clear width x height [mm]	1,552 x 1,740
Max. number of seats	8 + 1
Clearance circle [m]	16.5


All dimensions were measured on series-production vehicles. The heights stated here may vary by approx. ± 40 mm depending on fittings. The vehicle drawings are not true to scale. Not available in all countries. Available in different designs.

DIMENSIONS.

MAN TGE Minibus Long with High roof



MAN TGE Minibus Extra-long with High roof



Lateral sliding door, width x height [mm]	1,311 x 1,722
Rear hinged doors, clear width x height [mm]	1,552 x 1,740
Max. number of seats	18 + 1
Clearance circle [m]	16.5–17.0


Lateral sliding door, width x height [mm]	1,311 x 1,722
Rear hinged doors, clear width x height [mm]	1,552 x 1,740
Max. number of seats	18 + 1
Clearance circle [m]	16.5–17.0

Figures in brackets: with single tyres.

*Height dimension excludes roof-mounted air conditioning system. This is an optional extra and varies depending on the manufacturer. All dimensions determined are using standard vehicles. The heights stated here may vary by approx. ±40 mm depending on fittings. The vehicle drawings are not true to scale.

DIMENSIONS.


MAN TGE Chassis Standard with Chassis cab



Clearance circle [m]

13.9 – 14.2

MAN TGE Chassis Long with Chassis cab



Clearance circle [m]


16.5 – 17.0

Figures in brackets: with twin tyres.

All dimensions were measured on series-production vehicles. The heights stated here may vary by approx. ±40 mm depending on fittings. The vehicle drawings are not true to scale.

DIMENSIONS.

MAN TGE Chassis Extra-long with Chassis cab




Clearance circle [m]

16.5 – 17.0

All dimensions were measured on series-production vehicles. The heights stated here may vary by approx. ±40 mm depending on fittings. The vehicle drawings are not true to scale.

DIMENSIONS.


MAN TGE Chassis Standard with Crew cab



Clearance circle [m]

13.9 – 14.2

MAN TGE Chassis Long with Crew cab



Clearance circle [m]

16.5 – 17.0

Figures in brackets: with twin tyres.

All dimensions were measured on series-production vehicles. The heights stated here may vary by approx. ±40 mm depending on fittings. The vehicle drawings are not true to scale.

WEIGHTS.

MAN TGE Panel van

Driveline	Permissible gross vehicle weight [kg]	Engine rating [kW (PS)]	Max. trailer load, braked, on 12% gradient/unbraked [kg]	Permissible max. gross train weight [kg]	Permissible axle load, front/rear [kg]	Standard		Lang		Extralang	
						Min. dead weight [kg]	Payload capacity, max. [kg]	Min. dead weight [kg]	Payload capacity, max. [kg]	Min. dead weight [kg]	Payload capacity, max. [kg]
Front-wheel drive	3,000	75 (102)	2,500/750	5,500	1,800/2,100	2,022	978	–	–	–	–
		103 (140)	3,000/750	6,000	1,800/2,100	2,031	969	–	–	–	–
		130 (177)	3,000/750	6,000	1,800/2,100	2,040	960	–	–	–	–
Front-wheel drive	3,500	75 (102)	2,500/750	5,500	1,800*/2,100	2,022	1,478	2,153	1,347	2,233	1,267
		103 (140)	3,000/750	6,000	1,800*/2,100	2,031	1,469	2,161	1,339	2,241	1,259
		130 (177)	3,000/750	6,000	1,800*/2,100	2,040	1,460	2,170	1,330	2,250	1,250
All-wheel drive	3,000	103 (140)	3,000/750	6,000	1,800*/2,100	2,157	843	–	–	–	–
		130 (177)	3,000/750	6,000	1,800*/2,100	2,166	834	–	–	–	–
All-wheel drive	3,500	103 (140)	3,000/750	6,000	1,800*/2,100	2,157	1,343	2,287	1,213	2,358	1,142
		130 (177)	3,000/750	6,000	1,800*/2,100	2,166	1,334	2,296	1,204	2,367	1,133
Rear-wheel drive	3,500	103 (140)	3,500/750	7,000	1,800*/2,250	2,158	1,342	2,272	1,228	–	–
		130 (177)	3,500/750	7,000	1,800*/2,250	2,167	1,333	2,281	1,219	–	–
Rear-wheel drive	5,000	90 (122)	3,500/750	7,500	2,200/3,500	2,371	2,629	2,514	2,486	2,586	2,414
		130 (177)	3,500/750	8,000	2,200/3,500	2,380	2,620	2,524	2,476	2,595	2,405
Rear-wheel drive	5,500	90 (122)	3,500/750	7,500	2,200/4.000	2,371	2,242-3,129	2,514	1,990-2,986	2,586	1,907-2,798
		130 (177)	3,500/750	8,000	2,200/4.000	2,380	2,203-3,120	2,524	1,951-2,976	2,595	1,857-2,830
Electric drive	3,500	100 (136)	–	–	2,100/2,100	2,502	989	–	–	–	–

Roof loads

Model	Drawbar load [kg]
Normal roof	300
High roof	150
Super-high roof**	

Drawbar loads

at trailer load [kg]	Drawbar load [kg]	
	Front-wheel drive/ All-wheel drive	Rear-wheel drive
2,500	100	–
3,000	120	140
3,500	–	140

* Depending on equipment the permissible front axle load may rise to 2,100 kg. This may affect the minimum payload or the maximum payload capacity.

** For vehicles with the super-high roof, no specific roof load is designated ex-factory.

WEIGHTS.

MAN TGE Kombi

Driveline	Permissible gross vehicle weight [kg]	Engine rating [kW (PS)]	Max. trailer load, braked, on 12% gradient/unbraked [kg]	Permissible max. gross train weight [kg]	Permissible axle load, front/rear [kg]	Standard		Lang	
						Min. dead weight [kg]	Payload capacity, max. [kg]	Min. dead weight [kg]	Payload capacity, max. [kg]
Front-wheel drive	3,500	103 (140)	2,000/750	5,500	1,800*/2,100	2,149	1,351	2,295	1,205
		130 (177)	2,000/750	5,500	1,800*/2,100	2,158	1,342	2,304	1,196

Roof loads

Model	Drawbar load [kg]
Normal roof	300
High roof	150

Drawbar loads

at trailer load [kg]	Drawbar load [kg]
	Front-wheel drive
2,000	100

*Depending on equipment the permissible front axle load may rise to 2,100 kg. This may affect the minimum payload or the maximum payload capacity.

WEIGHTS.

MAN TGE Minibus

Driveline	Permissible gross vehicle weight [kg]	Engine rating [kW (PS)]	Max. trailer load, braked, on 12 % gradient/ unbraked [kg]	Permissible max. gross train weight [kg]	Permissible axle load, front/rear [kg]	Long		Extra long	
						Min. dead weight [kg]	Payload capacity, max. [kg]	Min. dead weight [kg]	Payload capacity, max. [kg]
All-wheel drive	4,000	103 (140)	3,000/750	6,000	2,100/2,100	2,835	1,013	–	–
	4,000	130 (177)	3,000/750	6,000	2,100/2,100	2,826	1,004	–	–
Rear-wheel drive	5,000	90 (122)	3,500/750	7,500	2,100/2,250	3,150	1,850	3,200	1,800
		130 (177)	3,500/750	8,000	2,100/2,250	3,160	1,840	3,210	1,790
Rear-wheel drive	5,500	90 (122)	3,500/750	7,500	2,200/4,000	3,160	2,340	3,210	2,290
		130 (177)	3,500/750	8,000	2,200/4,000	3,170	2,330	3,230	2,270

Roof loads

Model	Drawbar load [kg]
Normal roof	300
High roof	150

Drawbar loads

at trailer load [kg]	Drawbar load [kg]	
	Front-wheel drive/ All-wheel drive	Rear-wheel drive
3,000	120	–
3,500	–	140

WEIGHTS.

MAN TGE Chassis with Chassis cab

Driveline	Permissible gross vehicle weight [kg]	Engine rating [kW (PS)]	Max. trailer load, braked, on 12% gradient/unbraked [kg]	Permissible max. gross train weight [kg]	Permissible axle load, front/rear [kg]	Standard		Long		Extra long	
						Min. dead weight [kg]	Load capacity, max. [kg]	Min. dead weight [kg]	Load capacity, max. [kg]	Min. dead weight [kg]	Load capacity, max. [kg]
Front-wheel drive	3,000	75 (102)	2,500/750	5,500	1,800*/2,100	1,755	1,245	1,786	1,214	–	–
		103 (140)	3,000/750	6,000	1,800*/2,100	1,760	1,240	1,791	1,209	–	–
		130 (177)	3,000/750	6,000	1,800*/2,100	1,769	1,231	1,800	1,200	–	–
Front-wheel drive	3,500	75 (102)	2,500/750	5,500	1,800*/2,100	1,755	1,745	1,786	1,714	–	–
		103 (140)	3,000/750	6,000	1,800*/2,100	1,760	1,740	1,791	1,709	–	–
		130 (177)	3,000/750	6,000	1,800*/2,100	1,769	1,731	1,800	1,700	–	–
All-wheel drive	3,000	103 (140)	3,000/750	6,000	1,800*/2,100	1,883	1,117	1,914	1,086	–	–
		130 (177)	3,000/750	6,000	1,800*/2,100	1,892	1,108	1,923	1,077	–	–
All-wheel drive	3,500	103 (140)	3,000/750	6,000	1,800*/2,100	1,883	1,617	1,914	1,586	–	–
		130 (177)	3,000/750	6,000	1,800*/2,100	1,892	1,608	1,923	1,577	–	–
Rear-wheel drive	3,500	103 (140)	3,000/750	6,500	1,800*/2,250	1,968	1,532	2,012	1,488	2,026	1,474
		130 (177)	3,500/750	7,000	1,800*/2,250	1,977	1,523	2,021	1,479	2,035	1,465
Rear-wheel drive	5,000	90 (122)	3,500/750	7,500	2,200/3,500	1,999	3,001	2,050	2,950	2,066	2,934
		130 (177)	3,500/750	8,000	2,200/3,500	2,008	2,992	2,059	2,941	2,075	2,925
Rear-wheel drive	5,500	90 (122)	3,500/750	7,500	2,200/4,000	1,999	3,501	2,050	3,450	2,066	3,434
		130 (177)	3,500/750	8,000	2,200/4,000	2,008	3,492	2,059	3,441	2,075	3,425

Roof loads

Model	Drawbar load [kg]
Spoiler	50
Dachschlafkabine	100

Drawbar loads

at trailer load [kg]	Drawbar load [kg]	
	Front-wheel drive/All-wheel drive	Rear-wheel drive
2,500	100	–
3,000	120	140
3,500	–	140

* Depending on equipment the permissible front axle load may rise to 2,100 kg. This may affect the minimum payload or the maximum payload capacity.

WEIGHTS.

MAN TGE Chassis with Crew cab

Driveline	Permissible gross vehicle weight [kg]	Engine rating [kW (PS)]	Max. trailer load, braked, on 12 % gradient/ unbraked [kg]	Permissible max. gross train weight [kg]	Permissible axle load, front/rear [kg]	Standard		Long	
						Min. dead weight [kg]	Load capacity, max. [kg]	Min. dead weight [kg]	Load capacity, max. [kg]
Front-wheel drive	3,250	75 (102)	2,500/750	5,500	1,800*/2,100	1,886	1,364	1,922	1,328
		103 (140)	3,000/750	6,000	1,800*/2,100	1,892	1,358	1,927	1,323
		130 (177)	3,000/750	6,000	1,800*/2,100	1,900	1,350	1,936	1,314
Front-wheel drive	3,500	75 (102)	2,500/750	5,500	1,800*/2,100	1,886	1,614	1,922	1,578
		103 (140)	3,000/750	6,000	1,800*/2,100	1,892	1,608	1,927	1,573
		130 (177)	3,000/750	6,000	1,800*/2,100	1,900	1,600	1,936	1,564
All-wheel drive	3,500	103 (140)	3,000/750	6,000	1,800*/2,100	2,019	1,481	2,055	1,445
		130 (177)	3,000/750	6,000	1,800*/2,100	2,028	1,472	2,064	1,436
Rear-wheel drive	3,500	103 (140)	3,000/750	6,500	1,800*/2,250	1,981	1,519	2,027	1,473
		130 (177)	3,500/750	7,000	1,800*/2,250	1,991	1,509	2,037	1,463
Rear-wheel drive	5,000	90 (122)	3,500/750	7,500	2,200/3,500	2,104	2,896	2,158	2,842
		130 (177)	3,500/750	8,000	2,200/3,500	2,113	2,887	2,167	2,833
Rear-wheel drive	5,500	90 (122)	3,500/750	7,500	2,200/4,000	–	–	2,158	3,342
		130 (177)	3,500/750	8,000	2,200/4,000	–	–	2,167	3,333













Drawbar loads


at trailer load [kg]	Drawbar load [kg]	
	Front-wheel drive/All-wheel drive	Rear-wheel drive
2,500	100	–
3,000	120	140
3,500	–	140

* Depending on equipment the permissible front axle load may rise to 2,100 kg. This may affect the minimum payload or the maximum payload capacity.

TYRE LABEL.

MAN TGE Panel van

Summer tyres	Size	Rolling resistance	Wet grip	External rolling noise	Noise emission
	205/75 R 16 C 113/111	B	A	72 dB	
	235/65 R 16 C 115/113	B	B-A	72-70 dB	
	235/65 R 16 C 121/119	B	A	72 dB	
	205/70 R 17 C 115/113	C	B	72 dB	
	235/60 R 17 C 117/115	B	A	72 dB	
All-year tyres	Size	Rolling resistance	Wet grip	External rolling noise	Noise emission
	205/75 R 16 C 113/111	C	A	73 dB	
	235/65 R 16 C 115/113	B	A	73 dB	
	235/65 R 16 C 121/119	B	A	73 dB	
Winter tyres	Size	Rolling resistance	Wet grip	External rolling noise	Noise emission
	205/75 R 16 C 113/111	E	B	73 dB	
	235/65 R 16 C 115/113	E-C	B	73-71 dB	
	235/65 R 16 C 121/119	C	B	71 dB	
	205/70 R 17 C 115/113	C	B	73 dB	

 External rolling noise – A quieter tyre improves the ride comfort for you and radiates less noise to the environment. Ordering a particular make of tyre is not possible for logistical and production-related reasons.

COMMENTS.

Engines are fitted with a multi-step exhaust gas after-treatment system (diesel particulate system and SCR catalytic converter). The SCR catalytic converter (Selective Catalytic Reduction) selectively converts nitrogen oxide (NO_x) exhaust components into diatomic nitrogen (N₂) and water (H₂O). The conversion is carried out with the help of a synthetically-produced, water-based urea solution such as AdBlue® (ISO 22241-1/AUS 32), which is stored in an auxiliary tank. Depending on the vehicle, the customer must also refill the AdBlue® independently or have it refilled at the MAN Service-Partner between service intervals.

The consumption and emissions figures listed have been determined in accordance with the measuring method prescribed by law. Since 1 September 2017, certain new vehicles have already been type approved using the Worldwide Harmonized Light Vehicles Test Procedure, WLTP, a realistic test procedure for measuring fuel consumption and CO₂ emissions. Currently, the NEDC values are still being communicated for light commercial vehicles. In the case of new vehicles which have been type-approved according to the WLTP, the NEDC figures are derived from the WLTP data. In cases where the NEDC figures are specified as value ranges, these do not refer to a particular individual vehicle and do not constitute part of the sales offering.

Additional equipment and accessories (attachments, tyre size etc.) can change relevant vehicle parameters such as the weight, roll resistance and aerodynamics. In addition to weather and traffic conditions as well as the driver's specific driving behaviour, these features can influence the fuel consumption, the power consumption, the CO₂ emissions and the performance values of a vehicle.

Unladen vehicle weights listed here includes 68 kg for the driver, 7 kg for the luggage, all operating fluids and fuel tank 90 % full, determined in accordance with directive 92/21/EEC or directive 97/27/EC currently valid. Equipment or equipment lines may affect the unladen weight. A vehicle's actual payload, which results from calculating the difference between the gross vehicle weight and the unladen weight, can only be determined by weighing the individual vehicle.

GENERAL AND ADDITIONAL INFORMATION.

Please also bear in mind that some items of optional equipment are subject to certain combination constraints and/or cannot be combined with one another, and are also subject to certain legal regulations. MAN expressly disclaims all liability in connection with the misuse of these equipment features. Some options may result in longer delivery periods for the vehicle. Please discuss your specific requirements with a MAN dealer. Only your MAN dealer can assess the necessary combination requirements along with the correctness and completeness of the information using the available ordering system.

The fact that a trademark is not shown with a ® symbol in this document cannot be interpreted as meaning that this trademark is not a registered trademark and/or that this trademark can be used without prior approval in writing from MAN SE. The product name AdBlue is a registered trademark of the German Automotive Industry Association e. V. (VDA). iPod/iPad/iPhone are trademarks of Apple Inc.

Our vehicles are equipped with summer tyres as standard. Since 4 December 2010, drivers in the Federal Republic of Germany have been legally required to fit their vehicle with winter or all-weather tyres when driving on black ice, packed snow, slush, ice or icy frost. Your MAN dealer will be pleased to advise you.

All information and specifications provided in this document are based on the features of the German market and is in accordance with the information available at the time of going to print.

Additional information:

This technical data applies for the MAN TGE, model year 2019, as of 1 September 2018. Subject to change and errors.

Service appointments at MAN are classified as “oil change service” or “inspection”. The service interval display in the instrument cluster serves to remind the driver when the next service is due.

Return and recycling of end-of-life vehicles:

MAN meets the challenges of modern society and takes them into consideration in all new products of the MAN brand. This naturally also applies to protection of the environment and resources. Therefore, all new MAN TGE vehicles can be recycled in an environmentally-friendly way and, subject to fulfilment of legal prerequisites, can be returned free of charge. Further information about the return and recycling of end-of-life vehicles can be obtained from your MAN service partner.

Refrigerant R134a is used in vehicle classes N1, N2 and M2. The GWP value of the refrigerant used is 1.430 (refrigerant R134a). The quantities depend on the air conditioning compressor and vary between 560 - 590 grams.

MAN Truck & Bus AG

Postfach 50 06 20

D-80976 München

www.van.man

D115.006 · bv 03195

Text and illustrations are non-binding. Errors and omissions excepted. We reserve the right to make modifications. All specifications in this publication represent the status at the time of going to press.

MAN Truck & Bus – a member of the MAN Group